

# THE FUTURE OF AEROSPACE APPLICATIONS OF ADDITIVE MANUFACTURING: OPPORTUNITIES, OPTIMIZATION AND MODELING

#### Andrew A. Shapiro

John Paul Borgonia Nataly Chen

R. Peter Dillon

Samad Firdosy

Bryan McEnerney

**Richard Otis** 

Andre Pate

Jet Propulsion Laboratory, California Institute of Technology

# **OUTLINE**

Motivation

Modeling

**Design Optimization** 

A Brief Review of Aerospace Applications


Conclusion

March 2018

- Most additive models are developed independently
- · Optimization will be the key to better designs in the future
- We need to find the right applications


	DIN TILST ON THEM BAIGN DOGN DATA	
	SEE PRODUCT DATA MANAGEMBNT SYSTEM (PDMS) FOR APPROVAL SIG: DATES	natures and

### ADDITIVE MANUFACTURING MODELING




March 2018 5

### Atomistic / molecular dynamic modeling





### Kinetic modeling




#### Phase field modeling

No Evap. – Peak Temp around 33,000 K






Evap. – Peak Temp around 7000 K




X Axis




[Wolfer and Khairallah]
[UC Davis/ UC Irvine]

Z Axis (x10^-3)


### Thermodynamic modeling



### Off-equilibrium thermodynamic modeling



### Thermal modeling







LLNL-PRES-744280


[Nourgaliev et al., APS/DFD 2017, Denver, CO]


Residual stress modeling







#### **Process modeling**





[From LLNL-PRES-744280, UC Davis/UC Irvine]







[UC Davis/UC Irvine]
Ref. LLNL-PRES-707401]

March 2018 13


### Post-process modeling



### **ADDITIVE MANUFACTURING**




### ADDITIVE MANUFACTURING MODELING



March 2018 16

# **DESIGN OPTIMIZATION**

## **DESIGN OPTIMIZATION MODELING**





**MULTIPLE MATERIALS** 



SUBTRACTIVE DESIGN


LIGHTWEIGHT DESIGN


**GENERATIVE DESIGN** 


**TOPOLOGY OPTIMIZATION** 

March 2018 18


# **Topology Optimization**









# **Generative Design**





Protein Generation – N number of proteins







Cell adhesion








# **Subtractive Design**



# **Lightweight Design**


### 3-Dimensional Gridding, Scalable Gridding




# **Multiple Materials**

#### **Additive Gradient**

March 2018







23

# **Multifunctional Designs**

### 3-D and 4-D Multifunctional Systems



## DESIGN OPTIMIZATION MODELING



**MULTIFUNCTIONAL DESIGNS** 

**MULTIPLE MATERIALS** 



SUBTRACTIVE DESIGN

LIGHTWEIGHT DESIGN

**GENERATIVE DESIGN** 

**TOPOLOGY OPTIMIZATION** 

March 2018 29

# A BRIEF REVIEW OF AEROSPACE APPLICATIONS

# **Aerospace Areas Of Focus**

There are currently 7 areas of significant interest to aerospace that haven't received sufficient focus, yet offer significant benefits to their study

- 1. New Design Frontiers
  - Gradients
  - Ceramics
  - Multi-materials
  - Multi-functional Structures
- 2. Combination of Multiple Assemblies
- 3. High Complexity Parts
- 4. In-Situ Fabrication
- 5. Mass Reduction
- 6. A Tool for Materials Research & Tailoring
- 7. In Situ Resource Utilization




# **New Design Frontiers**

- Gradients creating axial- or radially-graded materials enables enhanced design, such as tailored thermal expansion, thermal conductivity, or weldability, where required within the structure
- Ceramics advanced properties, beyond purely structural (e.g. electrical, magnetic, dielectric) can be tailored as well
- Multi-materials multiple materials systems (ceramics, metals, polymers) within the same structural geometry
- Multi-functional Structures enabling smart structures with integrated functions such as embedded sensors within structural members
- Fabrics allow for flexible applications with multiple properties and materials




Image courtesy Ashley Reichardt under the direction of Professor Peter Hosemann, UC Berkeley under a contract for JPL



JPL Image by Raul Polit-Casillas

# **Combination of Multiple Assemblies**








- The elimination of joints through the intelligent combination of multiple parts, coupled with design optimization methodologies
- Eliminate or minimize welding/brazing, bolted or riveted designs, which can simultaneously reduce weight, cost, complexity, integration and schedule
- Design optimization can result in unique or organic part architectures that cannot be accomplished for the same cost using conventional processing methods

# **High Complexity Parts**

- A major thrust, that has been underutilized in aerospace, is the creation of high complexity parts that have both internally and externally complex features
- Complex functions can now be tailored to meet space constraints, such as multiple attachment points with 3-D flow passages








### **Mass Reduction**




- Mars Science Laboratory UHF Antenna Assembly
- Initial state (above left): 4-piece assembly with 6 bolted joints
- Final state (above right): 1-piece assembly
- 19% reduction in mass, as well as part count reduction

- Deep space exploration, and satellite launch, both have significant weight constraints (\$10,000/lb to low earth orbit)
- Reduction of mass and part count can provide significant cost benefits or enable greater capability for a number of missions, particularly landers where the weight reduction goals are even more extreme




# A Tool for Materials Research and Tailoring

- Development of new materials can be costly, particularly with more expensive alloy components or ceramic compositions.
  - Additive manufacturing allows for reduced material/lot sizes, which can enable research opportunities that otherwise may not be financially feasible
- Microstructural tailoring, which is impossible on a large scale for a number of processes, can be readily undertaken
  - In a single specimen, you can tailor a fatigue sensitive portion of a specimen with a fine-grained microstructure, whereas a coarse (e.g. faster build, slower dwell) microstructure will suffice for the remainder of the specimen, allowing micro-scale manipulation of the microstructure
  - The additive of selective agents, such as microspheres or toughening/hardening agents, akin to the original oxide dispersion strengthened superalloys, can be readily achieved and demonstrated for viability, further enabled by the rapid number of variations that can be procured in a single build










materials, with limited transported raw stock


Background image courtesy of NASA

### In Situ Resource Utilization



From: JPL/KSC Wilcox, Howe and Mueller

- Fabrication of structures autonomously for usage on foreign bodies
- Primary concepts envision human habitats, though exotic uses, such as a dark side of the moon space telescope platform are highly interesting
- Focus includes both process methodology as well as creative adaptation of available materials, with limited transported raw stock



#### **Acknowledgements**

This review paper was developed at the Jet Propulsion Laboratory, managed by the California Institute of Technology under a contract with NASA.

Special Thanks to Liz Barrios De La Torre for help with the graphics.

